


N 25 1867

Dial gauge stand PN 25 1867


1152				mm			
		1152	6mm.	180			

N 25 1857

Dial gauge stand PN 25 1857


1153				mm			
		1153		300			

Holder for micrometer

1160							
		1160					


CSN 25 1811.15 TOP QUALITY

Dial gauge ČSN EN ISO 46325 (ČSN 25 1811) TOP QUALITY RECOMMENDED for certification

1155.10			mm	mm	mm		
		1155.10	0-10	0,01	60		


CSN 25 1811CSN 25 1816

Dial gauge ČSN EN ISO 46325 (ČSN 25 1811, ČSN 25 1816)


	1155.12		mm	mm	mm		
		1155	0-10	0,01	60		
		1155.3	0-1	0,001	60		
		1155.1	0-25	0,01	60		
		1155.2	0-30	0,01	60		
		1158	0-5	0,01	40		
		<b>NEW</b> 1155.12	0-30	0,01	60		

- SHOK PROOF

Shock proof dial gauge


1157			mm	mm	mm		
		1157	0-10	0,01	60		

Digital gauge - NEW DESIGN

1155.6			mm	mm	mm		
		1155.5	0-12,7	0,01	60		
		1155.6	0-12,7	0,001	60		




**, PROFESIONAL**  
Digital gauge with data output, rotatate indicator, PROFESIONAL

1155.5.10 		mm	mm	mm		
	<b>NEW</b>	1155.5.10	0-12,7	0,01	60	12,9
	<b>NEW</b>	1155.6.10	0-12,7	0,001	60	12,9


**CSN 25 1811**

Dial gauge ČSN EN ISO 46325 (ČSN 25 1811) with lug

1155.4 		mm	mm	mm		
		1155.4	0-10	0,01	60	


**CSN 25 1820 -**

Dial test indicator ČSN EN ISO 46325 (ČSN 25 1820) - horizontal


1156 		mm	mm	mm			
		1156	(+ -) 0,8	0,01	40		
		1156.3	(+ -) 0,8	0,01	33		

**CSN 25 1820 -**

Dial test indicator ČSN EN ISO 46325 (ČSN 25 1820) - vertical


1156.2 		mm	mm	mm		
		1156.2	(+ -) 0,8	0,01	40	

Probe tips for indicators

1155.7 						
		1155.7	M 2,5mm	22		

**CSN 25 5548**

Support props for general use ČSN 25 5546-7 (ČSN 25 5548)

3035 			mm				
		3034	1	63			
		3035		80	14000N		
		3036		145	45000N		
		3037		205	70000N		