







CSN 25 1420 DIN 863

Outside micrometer ČSN 25 1420 DIN 863

		mm	mm			
7002		7002	0,01	0-25		
		7004	0,01	25-50		
7013		7006	0,01	50-75		
		7008	0,01	75-100		
		7011	0,01	100-125		
		7013	0,01	125-150		
7019		7015	0,01	150-175		
		7017	0,01	175-200		
		7019	0,01	200-225		
		7021	0,01	225-250		
7025.0		7023	0,01	250-275		
		7025	0,01	275-300		
		7025.0	0,01	100-200		
		7026.0	0,01	200-300		
7027		7026	0,01	300-400		
		7027	0,01	400-500		
		7027.1	0,01	500-600		
		7027.2	0,01	600-700		
		7027.3	0,01	700-800		
		7027.4	0,01	800-900		
7027.5	0,01	900-1000				

DIN 863, -


Screw thread micrometer DIN 863, with anvils

		mm	mm			
7028.31		7028.31	0,01	0-25	7028.41-5	
		7028.32	0,01	25-50	7028.42-6	
		7028.33	0,01	50-75	7028.43-6	
		7028.34	0,01	75-100	7028.43-6	
		7028.35	0,01	100-125	7028.43-6	
		7028.36	0,01	125-150	7028.43-6	

V-

60 °


V-shaped and knife anvils, metric thread 60°

			mm			
7028.41		7028.41	60°	0,4-0,5 mm		
		7028.42	60°	0,6-0,9 mm		
		7028.43	60°	1-1,75 mm		
		7028.44	60°	2-3 mm		
		7028.45	60°	3,5-5 mm		
		7028.46	60°	5,5-7 mm		



DIN 863


Digital outside micrometer DIN 863

<p>7030</p> 		mm	mm	μm		
	7030	0,001	0-25	4		
	7031	0,001	25-50	4		
	7032	0,001	50-75	5		
	7033	0,001	75-100	5		
	7034	0,001	100-125	6		
	7035	0,001	125-150	6		
	7036	0,001	150-175	7		
NEW	7037	0,001	175-200	7		

DIN 863,

, IP65

Digital outside micrometer DIN 863, data output, IP65


<p>7030.025</p> 		mm	mm	μm			
	NEW	7030.025	0,001	0-25	4		
	NEW	7030.050	0,001	25-50	4		
	NEW	7030.075	0,001	50-75	5		
NEW	7030.100	0,001	75-100	5			

DIN 863,ABS,

, ,


, IP65

Digital outside micrometer DIN 863, ABS, data output, rapid traverse, PROFESIONAL, IP65

<p>7031.025</p> 		mm	mm	μm			
	NEW	7031.025	0,001	0-25	4		
	NEW	7031.050	0,001	25-50	4		
	NEW	7031.075	0,001	50-75	5		
NEW	7031.100	0,001	75-100	5			


DIN 863

Digital thickness gauge DIN 863

<p>7040.1</p> 		mm	mm			
	7040.1	0,01	0-25			


CSN 25 1458 DIN 863

Tube micrometer ČSN 25 1458 DIN 863

<p>7041</p> 		mm	mm			
	7041	0,01	0-25			

CSN 25 1458 DIN 863


Micrometer special inserts ČSN 25 1458 DIN 863

<p>7002.1</p> 		mm	mm			
	7002.1	0,01	0-25			
	7002.2	0,01	0-25			




CSN 25 1456

Wire micrometer ČSN 25 1456

7043			mm	mm			
		7043	0,01	0-10			


CSN 25 1472 DIN 863

Disc micrometer ČSN 25 1472 DIN 863

7051			mm	mm			
		7051	0,01	0-25			
		7052	0,01	25-50			
		7053	0,01	50-75			
		7054	0,01	75-100			
		7055	0,01	100-125			
		7056	0,01	125-150			
		7057	0,01	150-175			
		7058	0,01	175-200			
		7059	0,01	200-225			
		7060	0,01	225-250			
		7061	0,01	250-275			
7062	0,01	275-300					


DIN 863

Digital disc micrometer DIN 863

7070.10			mm	mm	μm		
		7070.10	0,001	0-25	4		
		7070.11	0,001	25-50	4		
		7070.12	0,001	50-75	5		
		7070.13	0,001	75-100	5		

CSN 25 1430 DIN 863


Internal jaw micrometer ČSN 25 1430 DIN 863

7095			mm	mm			
		7095	0,01	5-30			
		7096	0,01	25-50			
		7097	0,01	50-75			
		7098	0,01	75-100			

Supplied without setting rings

DIN 863

Internal micrometer – jaw type DIN 863


7100.10			mm	mm	μm		
		7100.10	0,001 + .	5-30	4		
		7100.11	0,001 + .	25-50	4		
		7100.12	0,001 .	50-75	5		
		7100.13	0,001 .	75-100	5		

Bigger sizes of micrometers are available upon request




DIN 863

3-point internal micrometer set with setting rings DIN 863

7089.1		mm	mm			
	7089.1	0,005	6-12	6-8, 8-10, 10-12 8, 10		
	7089.2	0,005	11-20	11-14, 14-17, 17-20 11, 17		
	7089.3	0,005	20-40	20-25, 25-30, 30-35, 35-40 25, 35		
	7089.4	0,005	40-100	40-50, 50-60, 60-70, 70-80, 80-90, 90-100 50,70,90		

- DIN 863


3-point internal micrometer - DIN 863

7089.57		mm	mm	µm		
	7089.404	0,005	6-8	4		
	7089.405	0,005	8-10	4		
	7089.406	0,005	10-12	4		
	7089.407	0,005	11-14	4		
	7089.408	0,005	14-17	4		
	7089.409	0,005	17-20	4		
	7089.409.1	0,005	20-25	4		
	7089.409.2	0,005	25-30	4		
	7089.409.3	0,005	30-35	4		
	7089.409.4	0,005	35-40	4		
	7089.409.5	0,005	40-50	4		
	7089.41	0,005	50-60	5		
	7089.42	0,005	60-70	5		
	7089.420	0,005	70-80	5		
	7089.43	0,005	80-90	5		
	7089.44	0,005	90-100	5		
	7089.50	0,005	100-125	6		
	7089.51	0,005	125-150	6		
	7089.52	0,005	150-175	7		
	7089.53	0,005	175-200	7		
7089.54	0,005	200-225	8			
7089.55	0,005	225-250	8			
7089.56	0,005	250-275	9			
7089.57	0,005	275-300	9			




- DIN 863

Digital 3points internal micrometer – set DIN 863

7090.2 		mm	mm			
	7090.1	0,001	6-12	3pcs + 2pcs		
	7090.2	0,001	12-20	3pcs + 2pcs		
	7090.3	0,001	20-50	3pcs + 2pcs		
	7090.4	0,001	50-100	3pcs + 2pcs		


- DIN 863

Digital 3points internal micrometer - DIN 863

7090.50 		mm	mm	µm		
	7090.50	0,001	100-125	6		
	7090.51	0,001	125-150	6		
	7090.52	0,001	150-175	7		
	7090.53	0,001	175-200	7		


- DIN 863

Dial bore gauge with dial indicator DIN 863

7110.2 		mm	/			
			mm	mm		
	7110.0	0,01	6-10 / 40			
	7110.1	0,01	10-18 / 100			
	7110.2	0,01	18-35 / 150			
	7110.3	0,01	35-50 / 150			
	7110.4	0,01	50-100 / 150			
	7110.5	0,01	50-160 / 150			
	7110.6	0,01	100-250 / 250			
7110.7	0,01	250-400 / 250				

- DIN 863


Dial bore gauge with digital indicator DIN 863

7110.82 		mm	/		Specification	Price
			mm	mm		
	7110.80	0,01	6-10 / 40			
	7110.81	0,01	10-18 / 100			
	7110.82	0,01	18-35 / 150			
	7110.83	0,01	35-50 / 150			
	7110.84	0,01	50-100 / 150			
	7110.85	0,01	50-160 / 150			
	7110.86	0,01	100-250 / 250			
	7110.87	0,01	250-400 / 250			





- DIN 863

Dial bore gauge with dial indicator DIN 863

7110.92 		mm	/			
			mm	mm		
	7110.92	0,001	18-35 / 150			
	7110.93	0,001	35-50 / 150			
	7110.94	0,001	50-160 / 150			
7110.95	0,001	160-250 / 250				



Digital gauge available on request

Caliper gauge

7111.10 	7111.20 		mm			
				mm	mm	
		7111.10	0,01	15-35	3x3	
7111.20	0,01	0-20	6x3			

- DIN 863

Indicator micrometer DIN 863

7126 	7126.4 		mm	mm			
		7126	0,001	0-25			
		7126.0	0,001	0-25	+/- 60 SCALE		
		7126.1	0,001	25-50			
		7126.2	0,001	50-75			
		7126.3	0,001	75-100			
		7126.4	0,001	100-150			


CSN 25 1442 DIN 863

Depth micrometer ČSN 25 1442 DIN 863

7103 		mm	mm			
	7103	0,01	0-100			


DIN 863

Micrometer head DIN 863

7120 		mm	mm			
	7120	0,01	0-25			

CSN 25 1438 DIN 863

Internal micrometer ČSN 25 1438 DIN 863

7125 		mm	mm			
	7125	0,01	50-600			
	7125.0	0,01	50-75			
	7125.3	0,01	150-2500			

: 13, 25, 50, 100, 150, 200mm.

Length of extensions: 13, 25, 50, 100, 150, 200mm. Separately are available upon request